


NORTH

FLOOR PLAN
 SCALE: 3/16" = 1'-0"

LEGEND

- EXISTING PARTITION WALL TO REMAIN.
- NEW INTERIOR PARTITION WALL. 3 5/8" x 22 GA. METAL STUDS @ 16" O.C. TO UNDER SIDE OF FINISHED CEILING W/ 5/8" GYPSUM BOARD EACH SIDE. INFILL CAVITY WITH ACOUSTICAL BATT INSULATION. TAPE SMOOTH, AND PROVIDE LEVEL 5 FINISH. SEE A8.1 FOR WALL BRACING DETAIL.
- - - NEW INTERIOR PARTITION WALL. 3 5/8" x 22 GA. METAL STUDS @ 16" O.C. TO 3'-6" A.F.F. W/ 5/8" GYPSUM BOARD EACH SIDE. TAPE SMOOTH, AND PROVIDE LEVEL 5 FINISH. SEE A8.1 FOR WALL BRACING DETAIL.
- ⊕ EXISTING DUPLEX ELECTRICAL OUTLET OR NEW RECEPTACLE TO BE INSTALLED AS NOTED "N"
- ▲ EXISTING TEL/DATA RECEPTACLE OUTLET OR NEW RECEPTACLE TO BE INSTALLED AS NOTED "N"
- FE NEW EXPOSED OR SEMI-RECESSED FIRE EXTINGUISHER TO BE MOUNTED NO MORE THAN 48" A.F.F. TO EXTINGUISHER HANDLE.
- ⊗ CEILING MOUNTED EXIT SIGN TO REMAIN OR TO BE INSTALLED. CONTRACTOR TO VERIFY LOCATION IN FIELD.
- ⊙ OCCUPANCY SENSOR IN AREA NOTED TO COMPLY WITH LIGHT REDUCTION CONTROL PER IECC SECTION C405.2.1.1.

KEYED NOTES ○

1. NOT USED.

LEVEL 5 WALL FINISH (PER USG)

THE HIGHEST QUALITY FINISH IS THE MOST EFFECTIVE METHOD TO PROVIDE A UNIFORM SURFACE AND MINIMIZE THE POSSIBILITY OF JOINT PHOTOGRAPHING AND OF FASTENERS SHOWING THROUGH THE FINAL DECORATION. THIS LEVEL OF FINISH IS REQUIRED WHERE GLOSS, SEMIGLOSS OR ENAMEL ARE SPECIFIED, OR WHEN FLAT JOINTS ARE SPECIFIED OVER AN UNTEXTURED SURFACE, OR WHERE CRITICAL LIGHTING CONDITIONS OCCUR. THE PREPARED SURFACE SHALL BE COATED WITH A DRYWALL PRIMER PRIOR TO THE APPLICATION OF FINAL DECORATION.

ALL JOINTS AND INTERIOR ANGLES SHALL HAVE TAPE EMBEDDED IN JOINT COMPOUND AND IMMEDIATELY WIPED WITH A JOINT KNIFE OR TROWEL, LEAVING A THIN COATING OF JOINT COMPOUND OVER ALL JOINTS AND INTERIOR ANGLES. TWO SEPARATE COATS OF JOINT COMPOUND SHALL BE APPLIED OVER ALL FLAT JOINTS AND ONE SEPARATE COAT OF JOINT COMPOUND APPLIED OVER INTERIOR ANGLES. FASTENER HEADS AND ACCESSORIES SHALL BE COVERED WITH THREE SEPARATE COATS OF JOINT COMPOUND. A THIN SKIM COAT OF JOINT COMPOUND SHALL BE TROWEL APPLIED TO THE ENTIRE SURFACE. EXCESS COMPOUND IS IMMEDIATELY SHEARED OFF, LEAVING A FILM OR SKIM COATING OF COMPOUND COMPLETELY COVERING THE PAPER. AS AN ALTERNATIVE TO A SKIM COAT, A MATERIAL MANUFACTURED ESPECIALLY FOR THIS PURPOSE MAY BE APPLIED. THE SURFACE MUST BE SMOOTH AND FREE OF TOOL MARKS AND RIDGES. THE PREPARED SURFACE SHALL BE COVERED WITH A DRYWALL PRIMER PRIOR TO THE APPLICATION OF THE FINAL DECORATION.

NO.	REVISIONS	DATE

1010 S. ALLANTE PL.
 SUITE 100
 BOISE, IDAHO 83709
 (208) 336-8370
 FAX (208) 336-6380



PROPOSED DESIGN FOR:

VANILLA T.I.
 CORNERSTONE 450

913 W. RIVER ST #450
 BOISE, IDAHO

DRAWN	MLA
DATE	7/6/2020
CHECKED	MLA
JOB NO.	20047

FLOOR PLAN

A1.1